



DV M2 TNC 255 FM (956 305)

- Prewired spark-gap-based Type 1 + Type 2 + Type 3 combined arrester consisting of a base part and plug-in protection module
- Compact design while meeting the strictest safety requirements thanks to Rapid Arc Control (RAC)
- Enables protection of terminal equipment



Basic circuit diagram



Dimension drawing

Modular combined arrester for TN-C systems.

Type	DV M2 TNC 255 FM
Part No.	956 305
SPD according to EN 61643-11 / IEC 61643-11	Type 1 + type 2 + type 3 / class I + class II + class III
Energy coordination with terminal equipment (≤ 10 m)	Type 1 + Type 2 + Type 3
Nominal voltage (a.c.) (U_N)	230 / 400 V (50 / 60 Hz)
Max. continuous operating voltage (AC) (U_c)	255 V (50 / 60 Hz)
Lightning impulse current (10/350 μ s) [L1+L2+L3-PEN] (I_{total})	75 kA
Lightning impulse current (10/350 μ s) [L-PEN] (I_{imp})	25 kA
Specific energy [L-PEN] (W/R)	156.25 kJ/ohms
Nominal discharge current (8/20 μ s) [L-PEN] (I_n)	25 kA
Voltage protection level (U_p)	≤ 1.5 kV
Open-circuit voltage of the combination wave generator (U_{oc})	6 kV
Follow current extinguishing capability (a.c.) (I_R)	50 kA _{rms}
Follow current limitation / Selectivity	No tripping of a 35 A gG fuse up to 50 kA _{rms} (prosp.)
Short-circuit current rating [L-N]/[N-PE] (I_{SCCR})	50 kA _{rms}
Response time (t_A)	≤ 100 ns
Max. backup fuse	250 A gG
Temporary overvoltage (U_T) – characteristic	440 V / 120 min. – withstand
Let-through energy in combination with an MOV S20K275 ($I_{imp} = 2.5 \dots 25$ kA)	< 1 J
Operating temperature range [parallel]/[series] (T_U)	-40 °C ... +80 °C / -40 °C ... +60 °C
Operating state / fault indication	green / red
Number of ports	1
Cross-sectional area (L1, L2, L3, PEN,) (min.)	6 mm ² solid/fine-stranded
Cross-sectional area (L1, L2, L3, PEN,) (max.)	35 mm ² stranded / 25 mm ² fine-stranded
For mounting on	35 mm DIN rails acc. to EN 60715
Place of installation	Indoor
Degree of protection	IP 20
Capacity	4 Standard DIN module, DIN 43880
Approvals	VDE, KEMA, UL
Type of remote signalling contact	yes / changeover contact
Switching capacity (a.c.)	250 V / 0.5 A
Switching capacity (d.c.)	250 V / 0.1 A; 125 V / 0.2 A; 75 V / 0.5 A
Cross-sectional area for remote signalling terminals	max. 1.5 mm ² solid / fine-stranded
Extended technical data	
Max. prospective short-circuit current	100 kA _{rms} (220 kA _{peak})
Limitation / Extinction of mains follow currents	Up to 100 kA _{rms} (220 kA _{peak})
Arrester use at 16.7 Hz – traction power supply systems	
Test voltage AC (U_c)	266 V
Nominal AC voltage (U_N)	230 / 400 V
Nominal frequency AC (f_N)	16.7 Hz
Max. backup fuse	160 A gG @ 16,7 Hz

Masterdata

Net weight	459.38 g/pc(s)
Customs tariff number (Comb. Nomenclature EU)	85363090
GTIN	4013364510586
PU	1 pc(s)

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

¹⁾ See installation instructions for definition of S₂